

COMPOSICIÓN / COMPOSITION	SUPERFICIE / SURFACE	100% Poliéster / 100% Polyester
	BACKING / BACKING	100% Poliéster / 100% Polyester
GROSOR / THICKNESS		0.5 mm
LONGITUD/ LENGHT		50 m
ANCHO / WIDTH - ANCHO ÚTIL/ USABLE WIDTH		142 cm
PESO / WEIGHT		270 gsm
RESISTENCIA A LA ABRASIÓN / ABRASION RESISTANCE		50.000 Rubs
RESISTENCIA AL PILLING / PILLING RESISTANCE		4-5 ISO 12945-2
COLORANTES AZO / AZO DYE STUFF		No
SOLIDEZ AL FROTAMIENTO / RUBBING FASTNESS		Seco / dry 4,5 - húmedo / wet 3 (total 4) ISO 105-X12
REPELENTE A LAS MANCHAS / WATER REPELLENT		Sí / Yes
RESISTENCIA AL RASGADO / TEAR STRENGTH		Urdimbre/warp 135N- Trama/weft 260 N ISO 12936-2
SOLIDEZ A LA LUZ / FASTNESS TO LIGHT		4 ISO 105-B02
DESIZAMIENTO DE LA COSTURA / SEAM SLIPPAGE		Urdimbre/warp 2.4 MM - Trama/weft 3.8 MM ISO 12936-2
INSTRUCCIONES DE LAVADO / CARE INSTRUCTIONS		
		