

COMPOSICIÓN / COMPOSITION	SUPERFICIE / SURFACE	90% Poliéster / 10% Cotton
	BACKING / BACKING	100% Poliéster / 100% Polyester
GROSOR / THICKNESS		2 mm
LONGITUD/ LENGHT		35 m
ANCHO / WIDTH - ANCHO ÚTIL/ USABLE WIDTH		140 cm
PESO / WEIGHT		390 gsm
RESISTENCIA A LA ABRASIÓN / ABRASION RESISTANCE		over 25.000 cycles (until fabric broken) ISO 12947-1/2
RESISTENCIA AL PILLING / PILLING RESISTANCE		4 grade (2000 circles) ISO 12945-2
COLORANTES AZO / AZO DYE STUFF		No
SOLIDEZ AL FROTAMIENTO / RUBBING FASTNESS		Seco / dry 4 - húmedo / wet 3-4 ISO 105-X12
REPELENTE A LAS MANCHAS / WATER REPELLENT		Sí / Yes
RESISTENCIA AL RASGADO / TEAR STRENGTH		Urdimbre/Warp 88 N - Trama/Weft 64 N ISO 13937-3
DESLIZAMIENTO A LA COSTURA / SEAM SLIPPAGE		Urdimbre/Warp over<6 - Trama/Weft over<4 ISO 13936-1
SOLIDEZ A LA LUZ / FASTNESS TO LIGHT		4-5 (Total 5 grades) ISO 105-B02
INSTRUCCIONES DE LAVADO / CARE INSTRUCTIONS		