

COMPOSICIÓN / COMPOSITION	SUPERFICIE / SURFACE	100% Poliéster / 100% Polyester
	BACKING / BACKING	100% Poliéster / 100% Polyester
GROSOR / THICKNESS		1 mm
LONGITUD/ LENGHT		35-50 m
ANCHO / WIDTH - ANCHO ÚTIL/ USABLE WIDTH		140-145 cm
PESO / WEIGHT		270 gsm
RESISTENCIA A LA ABRASIÓN / ABRASION RESISTANCE		over 20.000 cycles (until fabric broken) ISO 12947-2
RESISTENCIA AL PILLING / PILLING RESISTANCE		4 grade ISO 12945-2
COLORANTES AZO / AZO DYE STUFF		No
SOLIDEZ AL FROTAMIENTO / RUBBING FASTNESS		Seco / dry 4-5 - húmedo / wet 4 105-X12
REPELENTE A LAS MANCHAS / WATER REPELLENT		Sí / Yes
RESISTENCIA AL RASGADO / TEAR STRENGTH		Urdimbre/Warp 48 N - Trama/Weft 41 N ISO 13937-3
DESLIZAMIENTO A LA COSTURA / SEAM SLIPPAGE		Urdimbre/Warp over 200 - Trama/Weft over 200 ISO 13936-1
SOLIDEZ A LA LUZ / FASTNESS TO LIGHT		3-4 (Total 5 grades) ISO 105-B02
INSTRUCCIONES DE LAVADO / CARE INSTRUCTIONS		
		