

KENTYA ● by Colorsane ●



COMPOSICIÓN / COMPOSITION	SUPERFICIE / SURFACE	100% Poliéster / 100% Polyester
	BACKING / BACKING	100% Poliéster / 100% Polyester
GROSOR / THICKNESS		1.1 mm
LONGITUD/ LENGHT		35-50 m
ANCHO / WIDTH - ANCHO ÚTIL/ USABLE WIDTH		140-142 cm
PESO / WEIGHT		310 gsm
RESISTENCIA A LA ABRASIÓN / ABRASION RESISTANCE		over 25.000 cycles (until fabric broken) ISO 12947-1/2
RESISTENCIA AL PILLING / PILLING RESISTANCE		4 grade (7000 circles) ISO 12945-3
COLORANTES AZO / AZO DYE STUFF		No
SOLIDEZ AL FROTAMIENTO / RUBBING FASTNESS		Seco / dry 4 - húmedo / wet 3 ISO 105-X12
REPELENTE A LAS MANCHAS / WATER REPELLENT		Sí / Yes
RESISTENCIA AL RASGADO / TEAR STRENGTH		Urdimbre/Warp 67 N - Trama/Weft 55 N ISO 13937-3
DESLIZAMIENTO A LA COSTURA / SEAM SLIPPAGE		Urdimbre/Warp 3 - Trama/Weft 3 ISO 13936-1
SOLIDEZ A LA LUZ / FASTNESS TO LIGHT		4 (Total 5 grades) ISO 105-B02

INSTRUCCIONES DE LAVADO / CARE INSTRUCTIONS

