

COMPOSICIÓN / COMPOSITION	SUPERFICIE / SURFACE	100% Poliéster / 100% Polyester
	BACKING / BACKING	100% Poliéster / 100% Polyester
GROSOR / THICKNESS		1.5 mm
LONGITUD/ LENGHT		30-50 m
ANCHO / WIDTH - ANCHO ÚTIL/ USABLE WIDTH		142 cm
PESO / WEIGHT		450 gsm
RESISTENCIA A LA ABRASIÓN / ABRASION RESISTANCE		over 25.000 cycles (until fabric broken) <b>ISO 12947-1/2</b>
RESISTENCIA AL PILLING / PILLING RESISTANCE		4 grade (2000 circles) <b>ISO 12945-2</b>
COLORANTES AZO / AZO DYE STUFF		No
SOLIDEZ AL FROTAMIENTO / RUBBING FASTNESS		Seco / dry 4-5 - húmedo / wet 4-5 <b>ISO 105-X12</b>
CIGARETTE TEST		Pass <b>B55852 PART 1 SOUCRE 0/ EN1021-1</b>
RESISTENCIA AL RASGADO / TEAR STRENGTH		Urdimbre/Warp 98.7 N - Trama/Weft 108.5 N <b>ISO 13937-3</b>
DESLIZAMIENTO A LA COSTURA / SEAM SLIPPAGE		Urdimbre/Warp over 4.89 - Trama/Weft over 4.7 <b>ISO 13936-2</b>
SOLIDEZ A LA LUZ / FASTNESS TO LIGHT		4 (Total 5 grades) <b>ISO 105-B02</b>
INSTRUCCIONES DE LAVADO / CARE INSTRUCTIONS		
		