

COMPOSICIÓN / COMPOSITION	SUPERFICIE / SURFACE	100% Poliéster / 100% Polyester
	BACKING / BACKING	100% Poliéster / 100% Polyester
GROSOR / THICKNESS		2 mm
LONGITUD/ LENGHT		30-50 m
ANCHO / WIDTH - ANCHO ÚTIL/ USABLE WIDTH		142 cm
PESO / WEIGHT		420 gsm
RESISTENCIA A LA ABRASIÓN / ABRASION RESISTANCE		over 30.000 cycles (until fabric broken) ISO 12947-1
RESISTENCIA AL PILLING / PILLING RESISTANCE		4-5 grade ISO 12945-2
COLORANTES AZO / AZO DYE STUFF		No
SOLIDEZ AL FROTAMIENTO / RUBBING FASTNESS		Seco / dry 4 - húmedo / wet 4-5 ISO 105-x12
REPELENTE A LAS MANCHAS / WATER REPELLENT		No
RESISTENCIA AL RASGADO / TEAR STRENGTH		Urdimbre/Warp 176N - Trama/Weft 164N ISO 13937-3
DESLIZAMIENTO A LA COSTURA / SEAM SLIPPAGE		Urdimbre/Warp over 1.2 - Trama/Weft over 5.3 ISO 13936-1
SOLIDEZ A LA LUZ / FASTNESS TO LIGHT		4-5 (21H) / 3-4 (40H) (Total 5 grades) ISO 105-B02

INSTRUCCIONES DE LAVADO / CARE INSTRUCTIONS

