

COMPOSICIÓN / COMPOSITION	SUPERFICIE / SURFACE	100% Poliéster / 100% Polyester
	BACKING / BACKING	100% Poliéster / 100% Polyester
GROSOR / THICKNESS		2 mm
LONGITUD/ LENGHT		30-50 m
ANCHO / WIDTH - ANCHO ÚTIL/ USABLE WIDTH		140-142 cm
PESO / WEIGHT		410 gsm +/- 10 gsm
RESISTENCIA A LA ABRASIÓN / ABRASION RESISTANCE		over 25.000 cycles (until fabric broken) ISO 12947-1/2
RESISTENCIA AL PILLING / PILLING RESISTANCE		4-5 grade (2000 circles) ISO 12945-1
COLORANTES AZO / AZO DYE STUFF		No
SOLIDEZ AL FROTAMIENTO / RUBBING FASTNESS		Seco / dry 4-5 - húmedo / wet 4-5 ISO 105-x12
REPELENTE A LAS MANCHAS / WATER REPELLENT		Sí / Yes
RESISTENCIA AL RASGADO / TEAR STRENGTH		Urdimbre/Warp 113.9 N - Trama/Weft 89.7 N ISO 13937-3
DESLIZAMIENTO A LA COSTURA / SEAM SLIPPAGE		Urdimbre/Warp over 1.5 - Trama/Weft over 2.1 ISO 12936-2
SOLIDEZ A LA LUZ / FASTNESS TO LIGHT		4 (Total 5 grades) ISO 105-B02
CIGARETTE TEST		Pass BS5852 PART 1 SOUCRE 0/ EN1021-1
INSTRUCCIONES DE LAVADO / CARE INSTRUCTIONS		