

ARTICLE	ARTÍCULO	SELENE
ROLL LENGTH	LONGITUD DE LA PIEZA	40 m
WIDTH	ANCHO	145 cm
USABLE WIDTH	ANCHO ÚTIL	140 cm
WEIGHT (m ²)	PESO (m ²)	400 gsm
WATER REPELLENT	REPELENTE A LAS MANCHAS	YES/SI
THICKNESS	ESPESOR	3 mm
COMPOSITION SURFACE	COMPOSICIÓN - SUPERFICIE	90% Polyester 10% Nylon
COMPOSITION BACKING	COMPOSICIÓN - BACKING	100% Polyester
ABRASION (MARTIN DALE)	ABRASIÓN (MARTIN DALE)	Over 20000 Rubs (BS EN ISO 12947-2: 2016)
PILLING	PILLING	4-5 (ISO 12945-1: 2000)
RUBBING FASTNESS DRY	SOLIDEZ AL FROTAMIENTO EN SECO	4-5 (ISO 105 X 12-2016)
RUBBING FASTNESS WET	SOLIDEZ AL FROTAMIENTO EN HÚMEDO	4-5 (ISO 105 X 12-2016)
TEAR STRENGTH WARP	RESISTENCIA AL DESGARRO URDIMBRE	112 N (ISO13937-3: 2000)
TEAR STRENGTH WEFT	RESISTENCIA AL DESGARRO TRAMA	71 N (ISO 13937-3: 2000)
FASTNESS TO LIGHT	SOLIDEZ A LA LUZ	Over 3 (ISO 105 B02-2014)
SEAM SLIPPAGE WARP	DESLIZAMIENTO COSTURA-URDIMBRE	Over 200 N (ISO13936.1:2004)
SEAM SLIPPAGE WEFT	DESLIZAMIENTO COSTURA-TRAMA	Over 200 N (ISO13936.1:2004)
AZO DYE STUF	COLORANTES AZO	NO
CARE INSTRUCTION RECOMENDATION	INSTRUCCIONES DE CUIDADO RECOMENDADAS	