

COMPOSICIÓN / COMPOSITION	SUPERFICIE / SURFACE	100% Poliéster / 100% Polyester
	BACKING / BACKING	100% Poliéster / 100% Polyester
GROSOR / THICKNESS		2 mm
LONGITUD/ LENGHT		30-50 m
ANCHO / WIDTH - ANCHO ÚTIL/ USABLE WIDTH		142 cm
PESO / WEIGHT		390+/- 10 gsm
RESISTENCIA A LA ABRASIÓN / ABRASION RESISTANCE		25.000 Rubs (Until fabric broken)
RESISTENCIA AL PILLING / PILLING RESISTANCE		4-5 grade(2000 circles) ISO 12945-2
COLORANTES AZO / AZO DYE STUFF		No
SOLIDEZ AL FROTAMIENTO / RUBBING FASTNESS		Seco / dry 4-5 - húmedo / wet 4-5 (total 5) ISO 105-X12
REPELENTE A LAS MANCHAS / WATER REPELLENT		Sí / Yes
RESISTENCIA AL RASGADO / TEAR STRENGTH		Urdimbre/warp 108.7 N- Trama/weft 76.8N
SOLIDEZ A LA LUZ / FASTNESS TO LIGHT		4(Total grade 5) ISO 105-B02
DESPLAZAMIENTO DE LA COSTURA / SEAM SLIPPAGE		Urdimbre/warp 2.5 MM - Trama/weft 2.5 MM
INSTRUCCIONES DE LAVADO / CARE INSTRUCTIONS		
		