

COMPOSICIÓN / COMPOSITION	SUPERFICIE / SURFACE	100% Poliéster / 100% Polyester
	BACKING / BACKING	100% Poliéster / 100% Polyester
GROSOR / THICKNESS		1.1 mm
LONGITUD/ LENGHT		30-60 m
ANCHO / WIDTH - ANCHO ÚTIL/ USABLE WIDTH		146 cm
PESO / WEIGHT		350 gsm
RESISTENCIA A LA ABRASIÓN / ABRASION RESISTANCE		Over 30.000 Rubs <small>ISO 12947-1,-2</small>
RESISTENCIA AL PILLING / PILLING RESISTANCE		4 <small>ISO 12945-2</small>
COLORANTES AZO / AZO DYE STUFF		No
SOLIDEZ AL FROTAMIENTO / RUBBING FASTNESS		Seco / dry 4-5 - húmedo / wet 3-4 <small>ISO 105-X12</small>
REPELENTE A LAS MANCHAS / WATER REPELLENT		Sí / Yes
RESISTENCIA AL RASGADO / TEAR STRENGTH		Urdimbre/warp 240N- Trama/weft 160N <small>ISO 12937-3</small>
SOLIDEZ A LA LUZ / FASTNESS TO LIGHT		4 <small>ISO 105-B02</small>
DESLIZAMIENTO DE LA COSTURA / SEAM SLIPPAGE		Urdimbre/warp - Trama/weft over 200 <small>ISO 12936-1</small>
RESISTENCIA A LA TRACCIÓN / TENSILE STRENGHT		Urdimbre/warp 1900 N - Trama/weft 1500N <small>ISO 12936-1</small>
CIGARETTE TEST		BS5852 part 1 Sourcre 0-NO PASS EN 1021-1- NO PASS

INSTRUCCIONES DE LAVADO / CARE INSTRUCTIONS

