

COMPOSICIÓN / COMPOSITION	SUPERFICIE / SURFACE	100% Poliéster / 100% Polyester
	BACKING / BACKING	100% Poliéster / 100% Polyester
GROSOR / THICKNESS		1.1 mm
LONGITUD/ LENGHT		30-60 m
ANCHO / WIDTH - ANCHO ÚTIL/ USABLE WIDTH		145 cm
PESO / WEIGHT		230 gsm
RESISTENCIA A LA ABRASIÓN / ABRASION RESISTANCE		Over 30.000 Rubs ISO 12947-1,-2
RESISTENCIA AL PILLING / PILLING RESISTANCE		4 ISO 12945-2
COLORANTES AZO / AZO DYE STUFF		No
SOLIDEZ AL FROTAMIENTO / RUBBING FASTNESS		Seco / dry 4 - húmedo / wet 3-4 ISO 105-X12
REPELENTE A LAS MANCHAS / WATER REPELLENT		Sí / Yes
RESISTENCIA AL RASGADO / TEAR STRENGTH		Urdimbre/warp 74N- Trama/weft 74N ISO 12937-3
SOLIDEZ A LA LUZ / FASTNESS TO LIGHT		4 ISO 105-B02
DESLIZAMIENTO DE LA COSTURA / SEAM SLIPPAGE		Urdimbre/warp 110 - Trama/weft 122 ISO 12936-1
RESISTENCIA A LA TRACCIÓN / TENSILE STRENGHT		Urdimbre/warp 670 N - Trama/weft 640N ISO 12936-1
CIGARETTE TEST		BS5852 part 1 Sourcre 0-NO PASS EN 1021-1- NO PASS

INSTRUCCIONES DE LAVADO / CARE INSTRUCTIONS

