

COMPOSICIÓN/ COMPOSITION	SUPERFICIE / SURFACE	100% Poliéster / 100% Polyester
	BACKING / BACKING	100% Poliéster / 100% Polyester
GROSOR / THICKNESS		1 mm
LONGITUD/ LENGHT		40-50 m
ANCHO / WIDTH - ANCHO ÚTIL/ USABLE WIDTH		140 cm
PESO / WEIGHT		270 gsm +- 10 gsm
RESISTENCIA A LA ABRASIÓN / ABRASION RESISTANCE		over 25.000 cycles (until fabric broken) ISO 12947-1/2
RESISTENCIA AL PILLING / PILLING RESISTANCE		4-5 grade (2000 circles) ISO 12945-2
COLORANTES AZO / AZO DYE STUFF		-
SOLIDEZ AL FROTAMIENTO / RUBBING FASTNESS		Seco / dry 4-5 - húmedo / wet 4-5 ISO 105-x12 (Total 5 grade) (Total 5 grade)
REPELENTE A LAS MANCHAS / WATER REPELLENT		Sí / Yes
RESISTENCIA AL RASGADO / TEAR STRENGTH		-
CIGARETTE TEST		Pass B55852 PART 1 SOUCRE 0/ EN1021-1
SOLIDEZ A LA LUZ / FASTNESS TO LIGHT		4-5 (Total 8 grades) ISO 105-B02
INSTRUCCIONES DE LAVADO / CARE INSTRUCTIONS		
		