

<b>COMPOSICIÓN / COMPOSITION</b>	<b>SUPERFICIE / SURFACE</b>	100% Poliéster / 100% Polyester
	<b>BACKING / BACKING</b>	100% Poliéster / 100% Polyester
<b>GROSOR / THICKNESS</b>		1.4 mm
<b>LONGITUD/ LENGHT</b>		30-60 m
<b>ANCHO / WIDTH - ANCHO ÚTIL/ USABLE WIDTH</b>		145 cm
<b>PESO / WEIGHT</b>		380 gsm
<b>RESISTENCIA A LA ABRASIÓN / ABRASION RESISTANCE</b>		Over 30.000 Rubs <small>ISO 12947-1,-2</small>
<b>RESISTENCIA AL PILLING / PILLING RESISTANCE</b>		4 <small>ISO 12945-2</small>
<b>COLORANTES AZO / AZO DYE STUFF</b>		No
<b>SOLIDEZ AL FROTAMIENTO / RUBBING FASTNESS</b>		Seco / dry 4-5 - húmedo / wet 4 <small>ISO 105-X12</small>
<b>REPELENTE A LAS MANCHAS / WATER REPELLENT</b>		Sí / Yes
<b>RESISTENCIA AL RASGADO / TEAR STRENGTH</b>		Urdimbre/warp 110- Trama/weft 94 <small>ISO 12937-3</small>
<b>SOLIDEZ A LA LUZ / FASTNESS TO LIGHT</b>		4 <small>ISO 105-B02</small>
<b>DESPLAZAMIENTO DE LA COSTURA / SEAM SLIPPAGE</b>		Urdimbre/warp - Trama/weft over 200 <small>ISO 12936-1</small>
<b>RESISTENCIA A LA TRACCIÓN / TENSILE STRENGHT</b>		Urdimbre/warp 1200 n - Trama/weft 690N <small>ISO 12936-1</small>
<b>CIGARETTE TEST</b>		BS5852 part 1 Sourcre 0-NO PASS EN 1021-1- NO PASS

**INSTRUCCIONES DE LAVADO / CARE INSTRUCTIONS**

