



**acualine**

antimanchas de última generación

O R N E L L A

STILO TEXTIL

ORNELLA ● by Stilo Textil.



|  |                                 |  |
|--|---------------------------------|--|
| <b>COMPOSICIÓN /<br/>COMPOSITION</b>                       | <b>SUPERFICIE /<br/>SURFACE</b> | <b>100% Poliéster / 100% Polyester</b>                                   |
|  | <b>BACKING /<br/>BACKING</b>    | <b>Fleece backing</b>  |
| <b>GROSOR /<br/>THICKNESS</b>                              |                                 | <b>1.5 mm</b>  |
| <b>LONGITUD/<br/>LENGHT</b>                                |                                 | <b>30-50 m</b>   |
| <b>ANCHO / WIDTH -<br/>ANCHO ÚTIL/ USABLE WIDTH</b>        |                                 | <b>142 CM/140 CM</b>   |
| <b>PESO /<br/>WEIGHT</b>                                   |                                 | <b>250 gsm / -10 gsm</b>   |
| <b>RESISTENCIA A LA ABRASIÓN /<br/>ABRASION RESISTANCE</b> |                                 | <b>Over 25000 rubs (until fabric broken)</b>                             |
| <b>RESISTENCIA AL PILLING /<br/>PILLING RESISTANCE</b>     |                                 | <b>4 grade (2000 circles)</b>  |
| <b>COLORANTES AZO /<br/>AZO DYE STUFF</b>                  |                                 | <b>no</b>  |
| <b>SOLIDEZ AL FROTAMIENTO /<br/>RUBBING FASTNESS</b>       |                                 | <b>Seco / dry 4-5 - húmedo /<br/>wet 4-5 (total grade 5 ISO 105-x12)</b> |
| <b>REPELENTE A LAS MANCHAS /<br/>WATER REPELLENT</b>       |                                 | <b>Sí / Yes</b>  |
| <b>RESISTENCIA AL RASGADO /<br/>TEAR STRENGTH</b>          |                                 | <b>Urdimbre/Warp 97.9 N -<br/>Trama/Weft 118.3 N ISO 13937-3</b>         |
| <b>DESlizAMIENTO A LA COSTURA /<br/>SEAM SLIPPAGE</b>      |                                 | <b>Urdimbre/Warp 2.5<br/>Trama/Weft over 2.1 ISO 12936-2</b>             |
| <b>SOLIDEZ A LA LUZ /<br/>FASTNESS TO LIGHT</b>            |                                 | <b>4 (total grade 5) ISO 105-B02</b>                                     |
| <b>CIGARETTE TEST</b>                                      |                                 | <b>BS5852 part Sourcre 0-PASS</b>  |
| <b>INSTRUCCIONES DE LAVADO /<br/>CARE INSTRUCTIONS</b>     |                                 |  |




**acualine**

antimanchas de última generación

Y V O N N E

STILO TEXTIL

|  |                         |   |
|--|-------------------------|---|
| COMPOSICIÓN /<br>COMPOSITION                       | SUPERFICIE /<br>SURFACE | 100% Poliéster / 100% Polyester   |
|  | BACKING /<br>BACKING    | Fleece backing  |
| GROSOR /<br>THICKNESS                              |                         | 2 mm  |
| LONGITUD/<br>LENGHT                                |                         | 30-50 m   |
| ANCHO / WIDTH -<br>ANCHO ÚTIL/ USABLE WIDTH        |                         | 142 CM/140 CM   |
| PESO /<br>WEIGHT                                   |                         | 240 gsm / -10 gsm   |
| RESISTENCIA A LA ABRASIÓN /<br>ABRASION RESISTANCE |                         | Over 20000 rubs (until fabric broken)   |
| RESISTENCIA AL PILLING /<br>PILLING RESISTANCE     |                         | 4 grade (2000 circles)  |
| COLORANTES AZO /<br>AZO DYE STUFF                  |                         | no  |
| SOLIDEZ AL FROTAMIENTO /<br>RUBBING FASTNESS       |                         | Seco / dry 4-5 - húmedo /<br>wet 4-5 (total grade 5 <b>ISO 105-x12</b> )            |
| REPELENTE A LAS MANCHAS /<br>WATER REPELLENT       |                         | Sí / Yes  |
| RESISTENCIA AL RASGADO /<br>TEAR STRENGTH          |                         | Urdimbre/Warp 108.4 N -<br>Trama/Weft 98.6 N ISO 13937-3                            |
| DESIZAMIENTO A LA COSTURA /<br>SEAM SLIPPAGE       |                         | Urdimbre/Warp 2.5<br>Trama/Weft over 2.8 <b>ISO 12936-2</b>                         |
| SOLIDEZ A LA LUZ /<br>FASTNESS TO LIGHT            |                         | 4 (total grade 5) <b>ISO 105-B02</b>  |
| CIGARETTE TEST                                     |                         | BS5852 part Sourcre 0-PASS  |
| INSTRUCCIONES DE LAVADO /<br>CARE INSTRUCTIONS     |                         |  |




# acualine

antimanchas de última generación

## A U R O R A



COLORSANE


|  |                                       |   |
|--|---------------------------------------|---|
| <b>COMPOSICIÓN /</b><br><b>COMPOSITION</b>                       | <b>SUPERFICIE /</b><br><b>SURFACE</b> | <b>100% Poliéster / 100% Polyester</b>  |
|  | <b>BACKING /</b><br><b>BACKING</b>    | <b>Fleece backing</b>   |
| <b>GROSOR /</b><br><b>THICKNESS</b>                              |                                       | <b>2.5 mm</b>   |
| <b>LONGITUD /</b><br><b>LENGHT</b>                               |                                       | <b>30-50 m</b>  |
| <b>ANCHO / WIDTH -</b><br><b>ANCHO ÚTIL / USABLE WIDTH</b>       |                                       | <b>142 CM/140 CM</b>  |
| <b>PESO /</b><br><b>WEIGHT</b>                                   |                                       | <b>240 gsm / -10 gsm</b>  |
| <b>RESISTENCIA A LA ABRASIÓN /</b><br><b>ABRASION RESISTANCE</b> |                                       | <b>Over 25000 rubs (until fabric broken)</b>  |
| <b>RESISTENCIA AL PILLING /</b><br><b>PILLING RESISTANCE</b>     |                                       | <b>4 grade (2000 circles)</b>   |
| <b>COLORANTES AZO /</b><br><b>AZO DYE STUFF</b>                  |                                       | <b>no</b>   |
| <b>SOLIDEZ AL FROTAMIENTO /</b><br><b>RUBBING FASTNESS</b>       |                                       | <b>Seco / dry 4-5 - húmedo /</b><br><b>wet 4-5 (total grade 5 ISO 105-x12)</b>      |
| <b>REPELENTE A LAS MANCHAS /</b><br><b>WATER REPELLENT</b>       |                                       | <b>Sí / Yes</b>   |
| <b>RESISTENCIA AL RASGADO /</b><br><b>TEAR STRENGTH</b>          |                                       | <b>Urdimbre/Warp 93.6 N -</b><br><b>Trama/Weft 91.4 N ISO 13937-3</b>               |
| <b>DESIZAMIENTO A LA COSTURA /</b><br><b>SEAM SLIPPAGE</b>       |                                       | <b>Urdimbre/Warp 1.9</b><br><b>Trama/Weft over 1.8 ISO 12936-2</b>                  |
| <b>SOLIDEZ A LA LUZ /</b><br><b>FASTNESS TO LIGHT</b>            |                                       | <b>4 (total grade 5) ISO 105-B02</b>  |
| <b>CIGARETTE TEST</b>  |                                       | <b>BS5852 part Sourcre 0-PASS</b>   |
| <b>INSTRUCCIONES DE LAVADO /</b><br><b>CARE INSTRUCTIONS</b>     |                                       |  |

*Premier Textil*  
I N T E R N A C I O N A L



T O K I O

TOKIO ● by Premier Textil ●

|  |                         |   |
|--|-------------------------|---|
| COMPOSICIÓN /<br>COMPOSITION                       | SUPERFICIE /<br>SURFACE | 100% Poliéster / 100% Polyester   |
|  | BACKING /<br>BACKING    | 100% Poliéster / 100% Polyeste  |
| GROSOR /<br>THICKNESS                              |                         | -   |
| LONGITUD/<br>LENGHT                                |                         | 45-55 m   |
| ANCHO / WIDTH -<br>ANCHO ÚTIL/ USABLE WIDTH        |                         | 142 CM/140 CM   |
| PESO /<br>WEIGHT                                   |                         | 270 gsm / -10 gsm   |
| RESISTENCIA A LA ABRASIÓN /<br>ABRASION RESISTANCE |                         | →30000  |
| RESISTENCIA AL PILLING /<br>PILLING RESISTANCE     |                         | 4-5   |
| COLORANTES AZO /<br>AZO DYE STUFF                  |                         | No  |
| SOLIDEZ AL FROTAMIENTO /<br>RUBBING FASTNESS       |                         | Seco / dry 4 - húmedo /<br>wet 4 <b>ISO 105-x12</b>                                 |
| REPELENTE A LAS MANCHAS /<br>WATER REPELLENT       |                         | No  |
| RESISTENCIA AL RASGADO /<br>TEAR STRENGTH          |                         | -   |
| DESILIZAMIENTO A LA COSTURA /<br>SEAM SLIPPAGE     |                         | -   |
| SOLIDEZ A LA LUZ /<br>FASTNESS TO LIGHT            |                         | 5 (total grade 8) <b>ISO 105-B02</b>  |
| CIGARETTE TEST                                     |                         | -   |
| INSTRUCCIONES DE LAVADO /<br>CARE INSTRUCTIONS     |                         |  |